



Capacity	Stroke	Model No.	Piston Area	Oil Volume	Collapsed Height A	Extended Height B	Cylinder Dia. D	Bore Dia. E	Plunger Dia. F	Port Height H	Stop Ring Height I	Saddle Dia. J	Clearance between saddle and stop ling L	Lock Nut Height K	Saddle Thickness S	Weight
Ton	mm		cm ²	cm ³	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
50	50	SLNT-502	86.6	433	220	270	145	105	80 × P8	30	40	80	20	10	35	23
	150	SLNT-506	86.6	1299	330	480	145	105	80 × P8	30	40	80	20	10	35	36
	300	SLNT-5012	86.6	2598	535	835	145	105	80 × P8	30	40	80	20	10	35	58
	500	SLNT-5020	86.6	4330	815	1315	145	105	80 × P8	50	40	80	20	10	35	89
100	50	SLNT-1002	154	770	260	310	185	140	110 × P8	40	45	110	20	10	50	48
	150	SLNT-1006	154	2309	360	510	185	140	110 × P8	40	45	110	20	10	50	65
	300	SLNT-10012	154	4618	545	845	185	140	110 × P8	40	45	110	20	10	50	99
	500	SLNT-10020	154	7697	835	1335	185	140	110 × P8	60	45	110	20	10	50	148
150	50	SLNT-1502	227	1135	290	340	225	170	135 × P8	50	50	135	20	10	60	104
	150	SLNT-1506	227	3405	390	540	225	170	135 × P8	50	50	135	20	10	60	138
	300	SLNT-15012	227	6809	555	855	225	170	135 × P8	50	50	135	20	10	60	195
	500	SLNT-15020	227	11349	855	1355	225	170	135 × P8	75	50	135	20	10	60	302
200	50	SLNT-2002	298.7	1493	320	370	265	195	155 × P8	60	60	155	25	10	70	123
	150	SLNT-2006	298.7	4480	420	570	265	195	155 × P8	60	60	155	25	10	70	158
	300	SLNT-20012	298.7	8959	580	880	265	195	155 × P8	60	60	155	25	10	70	215
	500	SLNT-20020	298.7	14932	875	1375	265	195	155 × P8	80	60	155	25	10	70	325
250	50	SLNT-2502	363.05	1815	350	400	290	215	170 × P10	65	65	170	25	10	80	162
	150	SLNT-2506	363.05	5446	450	600	290	215	170 × P10	65	65	170	25	10	80	203
	300	SLNT-25012	363.05	10892	605	905	290	215	170 × P10	65	65	170	25	10	80	268
	500	SLNT-25020	363.05	18153	895	1395	290	215	170 × P10	65	65	170	25	10	80	398
300	50	SLNT-3002	433.74	2169	365	415	320	235	190 × P10	70	70	190	25	10	85	210
	150	SLNT-3006	433.74	6506	465	615	320	235	190 × P10	70	70	190	25	10	85	261
	300	SLNT-30012	433.74	13012	635	935	320	235	190 × P10	70	70	190	25	10	85	351
	500	SLNT-30020	433.74	21687	955	1455	320	235	190 × P10	70	70	190	25	10	85	530
400	50	SLNT-4002	572.56	2863	400	450	370	270	220 × P10	85	80	220	30	10	95	306
	150	SLNT-4006	572.56	8588	500	650	370	270	220 × P10	85	80	220	30	10	95	375
	300	SLNT-40012	572.56	17177	660	960	370	270	220 × P10	85	80	220	30	10	95	488
	500	SLNT-40020	572.56	28628	985	1485	370	270	220 × P10	85	80	220	30	10	95	733
500	50	SLNT-5002	730.62	3653	445	495	410	305	250 × P12	95	90	250	30	10	110	417
	150	SLNT-5006	730.62	10959	545	695	410	305	250 × P12	95	90	250	30	10	110	501
	300	SLNT-50012	730.62	21919	710	1010	410	305	250 × P12	95	90	250	30	10	110	645
	500	SLNT-50020	730.62	36513	1015	1515	410	305	250 × P12	95	90	250	30	10	110	924
600	50	SLNT-6002	865.7	4329	475	525	450	332	270 × P12	100	100	270	30	10	120	533
	150	SLNT-6006	865.7	12986	575	725	450	332	270 × P12	100	100	270	30	10	120	635
	300	SLNT-60012	865.7	25971	745	1045	450	332	270 × P12	100	100	270	30	10	120	813
	500	SLNT-60020	865.7	43285	1050	1550	450	332	270 × P12	100	100	270	30	10	120	1149
800	50	SLNT-8002	1164.16	5812	535	585	520	385	320 × P12	120	115	320	30	10	135	804
	150	SLNT-8006	1164.16	17462	635	785	520	385	320 × P12	120	115	320	30	10	135	944
	300	SLNT-80012	1164.16	34925	805	1105	520	385	320 × P12	120	115	320	30	10	135	1185
	500	SLNT-80020	1164.16	58208	1100	1600	520	385	320 × P12	120	115	320	30	10	135	1622
1000	50	SLNT-10002	1452.2	7261	590	640	580	430	350 × P12	130	130	350	30	10	150	1097
	150	SLNT-10006	1452.2	21783	690	840	580	430	350 × P12	130	130	350	30	10	150	1254
	300	SLNT-100012	1452.2	43566	840	1140	580	430	350 × P12	130	130	350	30	10	150	1489
	500	SLNT-100020	1452.2	72610	1135	1635	580	430	350 × P12	130	130	350	30	10	150	2000
1200	50	SLNT-12002	1809.6	9048	670	720	650	480	390 × P12	145	145	390	35	10	165	1595
	150	SLNT-12006	1809.6	27143	770	920	650	480	390 × P12	145	145	390	35	10	165	1808
	300	SLNT-120012	1809.6	54287	920	1220	650	480	390 × P12	145	145	390	35	10	165	2127
	500	SLNT-120020	1809.6	90475	1170	1670	650	480	390 × P12	145	145	390	35	10	165	2682
1500	50	SLNT-15002	2206.2	11031	735	785	720	530	420 × P12	160	160	420	35	10	180	2146
	150	SLNT-15006	2206.2	33093	835	985	720	530	420 × P12	160	160	420	35	10	180	2403
	300	SLNT-150012	2206.2	66186	985	1285	720	530	420 × P12	160	160	420	35	10	180	2786
	500	SLNT-150020	2206.2	110309	1205	1705	720	530	420 × P12	160	160	420	35	10	180	3362