



Capacity	Stroke	Model No.	Piston Area	Oil Volume	Collapsed Height A	Extended Height B	Cylinder Dia. D	Bore Dia. E	Plunger Dia. F	Port Height H	Stop Ring Height I	Saddle Dia. J	Clearance between saddle and stop ling K	Lock Nut Height S	Weight
Ton	mm		cm <sup>2</sup>	cm <sup>3</sup>	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
50	50	DLNT-502	110	551	305	355	165	125	105xP8	75	40	95	45	35	42
	150	DLNT-506	110	1652	420	570	165	125	105xP8	75	50	95	45	35	60
	300	DLNT-5012	110	3304	580	880	165	125	105xP8	75	60	95	45	35	84
	500	DLNT-5020	110	5507	820	1320	165	125	105xP8	75	80	95	45	35	118
100	50	DLNT-1002	164.15	821	310	360	200	150	130xP8	75	40	115	45	40	66
	150	DLNT-1006	164.15	2462	430	580	200	150	130xP8	75	50	115	45	40	92
	300	DLNT-10012	164.15	4924	585	885	200	150	130xP8	75	60	115	45	40	125
	500	DLNT-10020	164.15	8207	825	1325	200	150	130xP8	75	80	115	45	40	177
150	50	DLNT-1502	234.84	1174	330	380	245	180	160xP10	85	40	145	45	50	106
	150	DLNT-1506	234.84	3522	445	595	245	180	160xP10	85	50	145	45	50	145
	300	DLNT-15012	234.84	7045	605	905	245	180	160xP10	85	60	145	45	50	198
	500	DLNT-15020	234.84	11742	845	1345	245	180	160xP10	85	80	145	45	50	278
200	50	DLNT-2002	294.53	1472	345	395	270	200	180xP10	85	40	165	50	60	134
	150	DLNT-2006	294.53	4418	460	610	270	200	180xP10	85	50	165	50	60	181
	300	DLNT-20012	294.53	8835	620	920	270	200	180xP10	85	60	165	50	60	246
	500	DLNT-20020	294.53	14726	860	1360	270	200	180xP10	85	80	165	50	60	346
250	50	DLNT-2502	373.85	1869	350	400	300	225	200xP10	85	40	185	50	70	172
	150	DLNT-2506	373.85	5608	465	615	300	225	200xP10	85	50	185	50	70	230
	300	DLNT-25012	373.85	11215	625	925	300	225	200xP10	85	60	185	50	70	309
	500	DLNT-25020	373.85	18692	865	1365	300	225	200xP10	85	80	185	50	70	430
300	50	DLNT-3002	443.16	2216	355	405	330	245	215xP10	85	40	195	50	75	211
	150	DLNT-3006	443.16	6647	470	620	330	245	215xP10	85	50	195	50	75	280
	300	DLNT-30012	443.16	13295	630	930	330	245	215xP10	85	60	195	50	75	396
	500	DLNT-30020	443.16	22158	870	1370	330	245	215xP10	85	80	195	50	75	519
400	50	DLNT-4002	582.57	2913	375	425	380	280	250xP12	85	40	230	60	85	294
	150	DLNT-4006	582.57	8738	490	640	380	280	250xP12	85	50	230	60	85	387
	300	DLNT-40012	582.57	17477	650	950	380	280	250xP12	85	60	230	60	85	515
	500	DLNT-40020	582.57	29128	890	1390	380	280	250xP12	85	80	230	60	85	707
500	50	DLNT-5002	716.29	3581	410	460	420	310	280xP12	95	45	260	65	95	400
	150	DLNT-5006	716.29	10744	520	670	420	310	280xP12	95	55	260	65	95	505
	300	DLNT-50012	716.29	21488	680	980	420	310	280xP12	95	60	260	65	95	662
	500	DLNT-50020	716.29	35814	915	1415	420	310	280xP12	95	80	260	65	95	895
600	50	DLNT-6002	869.44	4347	435	485	460	340	300xP12	100	50	280	65	105	501
	150	DLNT-6006	869.44	13041	545	695	460	340	300xP12	100	60	280	65	105	621
	300	DLNT-60012	869.44	26083	705	1005	460	340	300xP12	100	65	280	65	105	801
	500	DLNT-60020	869.44	43472	935	1435	460	340	300xP12	100	80	280	65	105	1061
800	50	DLNT-8002	1175.16	5876	485	535	530	395	340xP12	120	50	320	70	125	745
	150	DLNT-8006	1175.16	17627	585	735	530	395	340xP12	120	60	320	70	125	895
	300	DLNT-80012	1175.16	35254	750	1050	530	395	340xP12	120	65	320	70	125	1145
	500	DLNT-80020	1175.16	58757	975	1475	530	395	340xP12	120	80	320	70	125	1485
1000	50	DLNT-10002	1457	7284	525	575	595	440	380xP12	135	55	360	75	135	973
	150	DLNT-10006	1457	21854	630	780	595	440	380xP12	135	60	360	75	135	1218
	300	DLNT-100012	1457	43707	795	1095	595	440	380xP12	135	70	360	75	135	1538
	500	DLNT-100020	1457	72846	1020	1520	595	440	380xP12	135	85	360	75	135	1968
1200	50	DLNT-12002	1731	8655	555	605	650	480	420xP12	145	60	400	80	150	1290
	150	DLNT-12006	1731	25965	665	815	650	480	420xP12	145	70	400	80	150	1540
	300	DLNT-120012	1731	51930	825	1125	650	480	420xP12	145	75	400	80	150	1910
	500	DLNT-120020	1731	86551	1055	1555	650	480	420xP12	145	90	400	80	150	2440
1500	50	DLNT-15002	2211.68	11058	615	665	730	540	460xP12	165	65	440	85	170	1810
	150	DLNT-15006	2211.68	33175	725	875	730	540	460xP12	165	75	440	85	170	2120
	300	DLNT-150012	2211.68	66350	885	1185	730	540	460xP12	165	80	440	85	170	2570
	500	DLNT-150020	2211.68	110584	1125	1625	730	540	460xP12	165	100	440	85	170	3260